

LC26	347951.5699	391635.6469	Refer to 'SHD2326-SHD-HLG-GLEN-DR-EO-Lighting Layout-R2' S38 street lighting layout drawing	Proposed galvanised tubular steel lighting column of 6.0 metre nominal height with a planted base as supplied by Fabrikat and factory applied painted black finish (RAL9005) and post top mounted at 0° tilt. Thom Isaro Pro 6.74klm warm white 53w EWR LED luminaire in RAL 9005 finish, with Mayflower 2 node mounted in a 6 pin NEMA socket. Luminaire to be dimmed to 60% lumen output	Proposed IDNO supply connection	IDNO approved double pole isolator	N/A	N/A
------	-------------	-------------	--	--	---------------------------------	------------------------------------	-----	-----

SHD2326-SHD-HLG-GLEN-SH-EO-Lighting Schedule-R2

Proposed Unit No.	Easting Coordinates	Northing Coordinates	Unit Location	Unit Description	Service Connection Type	Primary Isolator	Secondary Isolator	Private Cable Network Termination Type
LC27	348013.8000	391622.0604	Refer to 'SHD2326-SHD-HLG-GLEN-DR-EO-Lighting Layout-R2' S38 street lighting layout drawing	Proposed galvanised tubular steel lighting column of 6.0 metre nominal height with a planted base as supplied by Fabrikat and factory applied painted black finish (RAL9005) and post top mounted at 0° tilt, Thorn Isaro Pro 6.74klm warm white 53w EWR LED luminaire in RAL 9005 finish, with Mayflower 2 node mounted in a 6 pin NEMA socket. Luminaire to be dimmed to 60% lumen output	Proposed IDNO supply connection	IDNO approved double pole isolator	N/A	N/A
LC28	348034.6604	391612.2788	Refer to 'SHD2326-SHD-HLG-GLEN-DR-EO-Lighting Layout-R2' S38 street lighting layout drawing	Proposed galvanised tubular steel lighting column of 6.0 metre nominal height with a planted base as supplied by Fabrikat and factory applied painted black finish (RAL9005) and post top mounted at 0° tilt, Thorn Isaro Pro 6.74klm warm white 53w EWR LED luminaire in RAL 9005 finish, with Mayflower 2 node mounted in a 6 pin NEMA socket. Luminaire to be dimmed to 60% lumen output	Proposed IDNO supply connection	IDNO approved double pole isolator	N/A	N/A
LC29	348064.0700	391593.2109	Refer to 'SHD2326-SHD-HLG-GLEN-DR-EO-Lighting Layout-R2' S38 street lighting layout drawing	Proposed galvanised tubular steel lighting column of 6.0 metre nominal height with a planted base as supplied by Fabrikat and factory applied painted black finish (RAL9005) and post top mounted at 0° tilt, Thorn Isaro Pro 6.74klm warm white 53w EWR LED luminaire in RAL 9005 finish, with Mayflower 2 node mounted in a 6 pin NEMA socket. Luminaire to be dimmed to 60% lumen output	Proposed IDNO supply connection	IDNO approved double pole isolator	N/A	N/A
LC30	348094.6300	391580.8531	Refer to 'SHD2326-SHD-HLG-GLEN-DR-EO-Lighting Layout-R2' S38 street lighting layout drawing	Proposed galvanised tubular steel lighting column of 6.0 metre nominal height with a planted base as supplied by Fabrikat and factory applied painted black finish (RAL9005) and post top mounted at 0° tilt, Thorn Isaro Pro 6.74klm warm white 53w EWR LED luminaire in RAL 9005 finish, with Mayflower 2 node mounted in a 6 pin NEMA socket. Luminaire to be dimmed to 60% lumen output	Proposed IDNO supply connection	IDNO approved double pole isolator	N/A	N/A
LC31	348119.5000	391581.3917	Refer to 'SHD2326-SHD-HLG-GLEN-DR-EO-Lighting Layout-R2' S38 street lighting layout drawing	Proposed galvanised tubular steel lighting column of 6.0 metre nominal height with a planted base as supplied by Fabrikat and factory applied painted black finish (RAL9005) and post top mounted at 0° tilt, Thorn Isaro Pro 6.74klm warm white 53w EWR LED luminaire in RAL 9005 finish, with Mayflower 2 node mounted in a 6 pin NEMA socket. Luminaire to be dimmed to 60% lumen output	Proposed IDNO supply connection	IDNO approved double pole isolator	N/A	N/A
LC32	348007.3185	391520.2204	Refer to 'SHD2326-SHD-HLG-GLEN-DR-EO-Lighting Layout-R2' S38 street lighting layout drawing	Proposed mid-hinged raise and lower galvanised tubular steel lighting column of 6.0 metre nominal height with a planted base, as supplied by Fabrikat and factory-applied painted black finish (RAL9005), and post-top mounted at 0° tilt, Thorn Isaro Pro 6.74klm warm white 53w EWR LED luminaire in RAL 9005 finish, with Mayflower 2 node mounted in a 6-pin NEMA socket. Luminaire to be dimmed to 50% lumen output	Proposed IDNO supply connection	IDNO approved double pole isolator	N/A	N/A
LC33	348040.7200	391506.8987	Refer to 'SHD2326-SHD-HLG-GLEN-DR-EO-Lighting Layout-R2' S38 street lighting layout drawing	Proposed mid-hinged raise and lower galvanised tubular steel lighting column of 6.0 metre nominal height with a planted base, as supplied by Fabrikat and factory-applied painted black finish (RAL9005), and post-top mounted at 0° tilt, Thorn Isaro Pro 6.74klm warm white 53w EWR LED luminaire in RAL 9005 finish, with Mayflower 2 node mounted in a 6-pin NEMA socket. Luminaire to be dimmed to 50% lumen output	Proposed IDNO supply connection	IDNO approved double pole isolator	N/A	N/A