

1 Luminaire data

1.1 Dextra Group PLC, DEXECO - OPUS COLUMN (OPUC L60 AS)

1.1.1 Data sheet

Manufacturer: Dextra Group PLC



OPUC L60 AS lanterns with posts DEXECO - OPUS COLUMN

Dexeco OPUC L60 AS - IP65 Column top mounted asymmetric LED luminaire, 5175 luminaire lumens matt grey weather resistant and salt spray tested paint finish. Diecast aluminium housing, injection moulded polycarbonate front cover, integral column spigot fixing mechanism included, supplied with 10m prewired flex to facilitate installation.

Options:

R11 DW - Dimming sensor with wide lens

PH - Photocell

NEM - NEMA Socket

OPUC 76mm SPIG - 76MM Spigot Fix

Luminaire data

Luminaire efficiency	: 100%
Luminaire efficacy	: 124.57 lm/W
Classification	: A30 ↓100.0% ↑0.0%
CIE Flux Codes	: 39 71 95 100 100
UGR 4H 8H	: 34.1 / 15.0
Control gear	: electronic ballast
Power	: 41.4 W
Luminous flux	: 5157 lm

Equipped with

Quantity	: 1
Designation	: Dextra
Colour	: 4000K
Luminous flux	: 5157 lm
Colour reproduction	: 2

Dimensions : 737 mm x 306 mm x 103 mm

