

ReachElite High Punch Powercore, IntelliHue 200

Date: _____
Type: _____
Firm Name: _____
Project: _____

**100 to 277 VAC, 5° Spread Lens, UL/
cUL, CE, CQC**

High-performance exterior long-throw floodlight with intelligent white and color light

ReachElite is a premium exterior long-throw luminaire designed to light large-scale outdoor structures ranging from bridges and facades to monuments and skyscrapers. Powerful enough to hit targets over 453 m (1,487 ft) away with the 300 W luminaire, ReachElite raises the bar for optical control, performance and beam quality in LED lighting. What sets ReachElite apart from the competition is its application efficiency, high punch, and adaptability. ReachElite delivers high-quality white and color light exactly where you want it. With a native beam angle under 3°, ReachElite introduces a new level of precision and punch to the premium exterior LED luminaire market.



- **High punch**—ReachElite's High Punch optical system enables the layering of precise high quality light. Increased application efficacy is realized as a result of high illuminance sources. As a result luminaires can be placed at far greater distances from surfaces to be illuminated. The native 2.6° beam angle allows for the light to hit targets up to 564 m (1,852 ft) away using the 300 W luminaire, without sacrificing light efficiency or quality.
- **Design flexibility**—ReachElite is available in three versions: 100 W, 200 W, and 300 W. Each luminaire contains either one, two, or three 100 W heads that can be aimed independently of each other. This empowers lighting designers to utilize multiple applications and beam direction in a single luminaire.
- **Flexible field-installed accessories**—Choose from a full line of high-quality accessories, from seven different spread lenses, a louver, full and half glare shields, a rock guard, and a slipfitter mount for all ReachElite luminaires. Color Kinetics accessories make project customization simple.
- **Integrates patented Powercore technology**—Patented Powercore controls power output to luminaires directly from line voltage - rapidly, efficiently, and accurately.
- **Design Ready**—Some items in this family are eligible for our fast access North American Design Ready program. Find out more at www.colorkinetics.com/global/design-ready-products
- **Application adaptability**—ReachElite High Punch excels in a wide range of lighting applications including spot lighting, and wall grazing. Optional secondary accessories combined with easy precise aiming bring ultimate in system flexibility to customize the look and performance of any project. Precision optical system allows for placement freedom.
- **Chromasync technology**—Improves color consistency between all LED luminaires within 2SDCM and simplifies commissioning. The color control algorithm utilizes active temperature measurement combined with the data measured during manufacturing each array.
- **Reliable**—ReachElite Powercore provides years of reliable use under rugged conditions. ReachElite offers more protection from corrosion by meeting ASTM B117 standard for > 1,500 hours of corrosion resistance and ANSI C136.31 with a 5G vibration rating (3G with Slipfitter mount), and elimination of water pooling on main cover lens and accessories.
- **Easily Controlled**—Works seamlessly with Color Kinetics controllers, including Light System Manager, Video System Manager, Video System Manager Pro, iPlayer 3, Antumbra iColor Keypad, and ColorDial Pro, as well as third-party controllers.

For detailed product information, please refer to the ReachElite Product Guide at www.colorkinetics.com/global/products/intellihue/reachelite-intellihue-powercore/

Specifications

Due to continuous improvements and innovations, specifications may change without notice.

Output

Beam Angle	5°
Lumens All Channels Full On†	7,646
Efficacy (lm/W) All Channels Full On	38.1
CRI All Channels Full On	71
LED Channels	Red/Green/Blue/Mint White

Electrical

Input Voltage	100 to 277 VAC, auto-ranging, 50/60 Hz
Power Consumption (Maximum at full output, steady state)	200 W
Power Factor	0.99 @ 120 VAC 0.90 @ 277 VAC
Surge Limits¶	2 kV maximum differential (L to N) 4 kV maximum common (L to Gnd or N to Gnd)

For additional Surge Protection Requirements for LED Lighting Systems, please refer to www.colorkinetics.com/KB/surge-protection.

Control

Interface	Data Enabler Pro (DMX/Ethernet)
-----------	---------------------------------

Control System

Color Kinetics full range of controllers, including Light System Manager, Video System Manager Pro, iPlayer 3, Antumbra iColor Keypad, and ColorDial Pro, or third-party controllers

Remote Monitoring & Management	Philips ActiveSite Ready, works with Interact Landmark
--------------------------------	--

Lumen Maintenance

Threshold§	Ambient Temperature	Reported¶¶	Calculated¶¶
L ₉₀	25 °C	23,100	23,100
	50 °C	23,100	23,100
L ₈₀	25 °C		67,000
	50 °C	> 51,000	67,000
L ₇₀	25 °C	> 51,000	> 100,000
	50 °C	> 51,000	> 100,000
L ₅₀	25 °C	> 51,000	> 100,000
	50 °C	> 51,000	> 100,000

† ReachElite High Punch 100 lumen output measurements comply with IES LM-79-08 testing procedures. ReachElite High Punch 200 measurements are estimated based on the ReachElite High Punch 100 measurements.

§ L_{xx} = xx% lumen maintenance (when light output drops below xx% of initial output). All values are given at B10, or the median value where 90% of the LED population is better than the reported or calculated lumen maintenance measurement.

¶ Minimum surge limits per IEC 61547, tested in accordance with IEC 61000-4-5.

¶¶ Lumen maintenance figures are based on lifetime prediction graphs supplied by LED source manufacturers. Whenever possible, figures use measurements that comply with IES LM-80-08 testing procedures. In accordance with TM-21-11, Reported values represent the interpolated value based on six times the LM-80-08 total test duration (in hours). Calculated values represent time durations that exceed six times the total test duration.

Physical

Dimensions (Height x Width x Depth)	344.2 x 702.8 x 406 mm (13.56 x 27.68 x 16 in)
Weight	28 kg (61.7 lb)
Effective Projected Area (EPA)	0.252 m² (2.71 ft²) With full glare shield.
Housing Material	Die-cast aluminium, black powder-coated finish
Lens	Clear tempered glass
Luminaire Connections	Integral male/female waterproof connector

Temperature Ranges

-40 to 50 °C (-40 to 122 °F) Operating
-20 to 50 °C (-4 to 122 °F) Startup
-40 to 80 °C (-40 to 176 °F) Storage

Vibration Resistance

ANSI C136.31 with a 5G vibration rating (3G with Slipfitter mount)

Mechanical Impact	IK09 (IK10 with Louver or Wire Rock Guard accessory.)
-------------------	---

Corrosion Resistance

Complies with ASTM B117 standard for > 1,500 hours

Humidity	0 to 95%, non-condensing
----------	--------------------------

Luminaire Run Lengths

To calculate luminaire run lengths and total power consumption for your specific installation, download the Configuration Calculator from www.colorkinetics.com/support/install_tool/


Certification and Safety

Approbation	UL/cUL, FCC Class A, CE, PSE, CQC, RCM
Environment	Dry/Damp/Wet Location, IP66

For additional Energy Efficiency Class Information, please refer to <https://colorkinetics.helpdocs.io/article/cviis2p8qq>.



Dimensions




Photometrics 100 W, 5° Spread Lens

Photometric data is based on test results from an independent NIST traceable testing lab. IES data is available at www.colorkinetics.com/global/support/ies.

Beam Angle	5°
LEDs	All channels full on
Lumens All Channels Full On	3,823
Efficacy (lm/W) All Channels Full On	38.1



Polar Candela Distribution



	0	25	45	70	90
0	189377	189377	189377	189377	189377
5	22696	24115	26711	30881	33986
15	1236	1272	1306	1348	1398
25	395	411	425	402	398
35	196	217	233	196	189
45	117	139	149	122	119
55	72	78	83	73	73
65	34	34	35	36	36
75	12	12	11	12	11
85	1	1	1	1	0
90	0	0	0	0	0

Illuminance at Distance

	Center Beam fc	Beam Width
4 ft	11,836.00 fc	0.4 ft 0.4 ft
8 ft	2,959.02 fc	0.8 ft 0.8 ft
12 ft	1,315.12 fc	1.3 ft 1.3 ft
16 ft	739.75 fc	1.7 ft 1.7 ft
20 ft	473.44 fc	2.1 ft 2.1 ft
24 ft	328.78 fc	2.5 ft 2.5 ft

435 ft (132.6 m)
1 fc maximum distance

■ Vert. Spread: 6.0°
■ Horiz. Spread: 6.0°

Zonal Lumen

Zone	Lumens	% Luminaire
0-30	3465.6	90.6%
0-40	3601.6	94.2%
0-60	3772.2	98.7%
60-90	51.0	1.3%
70-100	14.8	0.4%
90-120	0.0	0.0%
0-90	3823.2	100.0%
90-180	0.0	0.0%
0-180	3823.2	100.0%

For lux multiply fc by 10.7

Coefficients of Utilization - Zonal Cavity Method

	Effective Floor Cavity Reflectance: 20%															
RCC %:	80	70	50	30	10	0										
RW %:	70	50	30	0	70	50	30	0	50	30	20	50	30	20	50	30
RCR:																
0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.00	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02
1	1.16	1.14	1.12	1.10	1.13	1.12	1.10	0.98	1.08	1.06	1.05	1.04	1.03	1.02	1.01	1.00
2	1.12	1.09	1.07	1.04	1.10	1.08	1.05	0.96	1.05	1.03	1.01	1.02	1.00	0.99	0.99	0.98
3	1.10	1.06	1.03	1.00	1.08	1.04	1.02	0.94	1.02	1.00	0.98	1.00	0.98	0.96	0.96	0.95
4	1.07	1.03	0.99	0.97	1.06	1.02	0.99	0.93	1.00	0.97	0.95	0.98	0.96	0.94	0.96	0.95
5	1.05	1.00	0.97	0.94	1.04	0.99	0.96	0.91	0.98	0.95	0.93	0.98	0.94	0.92	0.95	0.93
6	1.03	0.98	0.95	0.92	1.02	0.97	0.94	0.90	0.96	0.93	0.91	0.95	0.93	0.91	0.94	0.92
7	1.01	0.96	0.93	0.91	1.00	0.96	0.93	0.89	0.95	0.92	0.90	0.94	0.91	0.89	0.93	0.91
8	1.00	0.95	0.91	0.89	0.99	0.94	0.91	0.88	0.93	0.91	0.89	0.92	0.90	0.88	0.92	0.90
9	0.98	0.93	0.90	0.88	0.96	0.93	0.90	0.87	0.92	0.89	0.88	0.91	0.89	0.87	0.91	0.89
10	0.97	0.92	0.89	0.87	0.96	0.92	0.89	0.86	0.91	0.88	0.87	0.91	0.88	0.87	0.90	0.88

Luminaire and Accessories

Use Item Number when ordering in North America

Luminaire	Item Number	Item 12NC
ReachElite High Punch Powercore, IntelliHue 200, 100 to 277 VAC, 5° Spread Lens, UL/cUL, CE, CQC <i>Luminaire only. Leader cable sold separately.</i>	423-000203-02	912400135522
Associated Part		
Spread Lens With Trim Bezel, 5°	120-000197-06	912400135536
Accessories		
Slipfitter Mount, 2-3/8in	120-000197-04	912400135534
Louver	120-000197-02	912400135532
Rock Guard	120-000197-03	912400135533
Half Glare Shield	120-000197-01	912400135531
Full Glare Shield	120-000197-00	912400135530
Spread Lens With Trim Bezel, 10°	120-000197-07	912400135537
Spread Lens With Trim Bezel, 20°	120-000197-08	912400135538
Spread Lens With Trim Bezel, 40°	120-000197-09	912400135539
Spread Lens With Trim Bezel, 60°	120-000197-10	912400135540
Spread Lens With Trim Bezel, 80°	120-000197-11	912400135541
Spread Lens With Trim Bezel, 10° x 40°	120-000197-12	912400135542
Leader Cable, 50 ft, UL	108-000055-00	910503703137
Leader Cable, 50 ft, CE	108-000055-01	910503704064
Leader Cable, 50 ft, CCC	108-000055-02	910503704065
Leader Cable, 10 ft, UL	108-000055-03	910503704066
Leader Cable, 10 ft, CE	108-000055-04	910503704067
Leader Cable, 10 ft, CCC	108-000055-05	910503704068
Power/Data Supplies		
Data Enabler Pro, 3/4 in / 1/2 in NPT (U.S. trade size conduit)	106-000004-00	910503701210
Data Enabler Pro, PG21/PG13 (metric size conduit)	106-000004-01	910503701211



© 2021 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

Color Kinetics
www.colorkinetics.com/global/products/intelliHue/reachelite-intelliHue-powercore/