
From: Huseyin Utku <huseyinutku01@gmail.com>
Sent: 04 July 2023 14:49
To: Quinn, Mark
Subject: External Mail: Ventilation strategy for 9 Tarbock Rd 04-07-2023.pdf
Attachments: Ventilation strategy for 9 Tarbock Rd 04-07-2023.pdf

CAUTION: This email originated from an external source. If you suspect a potential phishing email, report it via the IT Self Service Portal which can be found within the Quick Links section on Bertha



Stainless Steel Fabrication

Commercial Kitchen Design and Installation

Ventilation strategy for the below address

Address

9 Tarbock Rd
Huyton,
Liverpool
L36 5XN

Installation of extraction system proposed at the above address to *EMAQ Guidance Control of Odour and Noise from Commercial Kitchen Exhaust Systems*

All canopy and ductwork to *BESA DW172 DW144*

Canopy dimensions to Dw172

Canopy Dimensions

3.7Mtr x 1200mm x 500mm x 430mm

Filtration

Longar type 3 baffle filters

Odour control

1 x double pass Carbon filter unit 0.8 sec dwell time

1 x mesh filter 495 x 495 x 50mm

1 x G4 Pleated filter 495 x 495 50mm



Stainless Steel Fabrication
Commercial Kitchen Design and Installation

UNIT 5 FIREFLY SQUARE PLANTATION ROAD BURSCOUGH L408JT

Tel: 01704-893945 Fax: 0844-4122296

Email: fusionhot1@gmail.com Web: www.facebook.com/fusionhot

Stainless Steel Fabrication Commercial Kitchen Design and Installation

Extract fan

Fan Model	Maximum absorbed power (W)	Maximum absorbed current (A)		Maximum air volume (m3/h)	Sound pressure level* (dB(A))	Speed (r.p.m.)	Weight (Kg)
		230v	400v				
TCBB/4-450H	526	1.9	1.1	6650	63	1405	21

Attenuation Octave – Band Mid Frequencies (Hz)

Diameter	Length	63	125	250	500	1000	2000	4000	8000
RSA(F) 450/450	450	0	1	4	12	12	9	6	6
RSA(F) 450/900	900	0	1	7	21	21	15	10	8

Cleaning and maintenance

Cleaning and maintenance schedule to be supplied to client to TR19 guidelines

FUSIONHOT



Stainless Steel Fabrication
Commercial Kitchen Design and Installation

UNIT 5 FIREFLY SQUARE PLANTATION ROAD BURSCOUGH L408JT


Tel: 01704-893945 Fax: 0844-4122296

Email: fusionhot1@gmail.com Web: www.facebook.com/fusionhot

Stainless Steel Fabrication Commercial Kitchen Design and Installation

This must be carried out by a competent registered BESA Ductwork cleaner no longer than 12 month intervals or earlier

Typical extraction canopy's below



Stainless Steel Fabrication Commercial Kitchen Design and Installation

Risk Assessment for Odour EMAQ

Odour control must be designed to prevent odour nuisance in a given situation. The following score methodology is suggested as a means of determining odour control requirements using a simple risk assessment approach. The odour control requirements considered here are consistent with the performance requirements listed in this report.

Criteria	Score	Score	Details
Dispersion	Very poor	20	Low level discharge, discharge into courtyard or restriction on stack.
	Poor	15	Not low level but below eaves, or discharge at below 10 m/s.
	Moderate	10	Discharging 1m above eaves at 10 -15 m/s.
	Good	5	Discharging 1m above ridge at 15 m/s.
Proximity of receptors	Close	10	Closest sensitive receptor less than 20m from Kitchen discharge.
	Medium	5	Closest sensitive receptor between 20 and 100m from kitchen discharge.
	Far	1	Closest sensitive receptor more than 100m from kitchen discharge ¹ .
Size of kitchen	Large	5	More than 100 covers or large sized take away.
	Medium	3	Between 30 and 100 covers or medium sized take away.
	Small	1	Less than 30 covers or small take away ¹ .
Cooking type (odour and grease loading)	Very high	10	Pub (high level of fried food), fried chicken, burgers or fish & chips. <i>Turkish, Middle Eastern or any premises cooking with solid fuel</i>
	High	7	Vietnamese, Thai, Indian, Japanese, Chinese, <i>steakhouse</i>
	Medium	4	Cantonese, <i>Italian, French, Pizza (gas fired),</i>
	Low	1	Most pubs (<i>no fried food, mainly reheating and sandwiches etc</i>), <i>Tea rooms</i> ¹



Stainless Steel Fabrication

Commercial Kitchen Design and Installation

Premises type	Dispersion	Proximity of receptors	Size of Kitchen	Cooking Type	Total Score
Restaurant	10	10	3	10	33

Impact Risk	Odour Control Requirement	Significance Score*
Low to Medium	Low level odour control	Less than 20
High	High level odour control	20 to 35
Very High	Very high level odour control	More than 35
* based on the sum of contributions from dispersion, proximity of receptors, size of kitchen and cooking type:		



Stainless Steel Fabrication
Commercial Kitchen Design and Installation

UNIT 5 FIREFLY SQUARE PLANTATION ROAD BURSCOUGH L408JT

Tel: 01704-893945 Fax: 0844-4122296

Email: fusionhot1@gmail.com Web: www.facebook.com/fusionhot

CYLINDRICAL CASED AXIAL FLOW FANS

COMPACT TCBB / TCBT series - ALUMINIUM IMPELLERS

Range of cylindrical cased axial flow fans fitted with aluminium impellers and manufactured from high grade rolled galvanised steel and protected against corrosion by cataforesis primer and black polyester paint finish.

All models are supplied with pre-wired wiring junction box located on the outside of the fan casing for easy wiring access. Available with 4 pole single or three phase motors.

Motors

Single phase motor (TCBB) or three phase motor (TCBT).

Models 250, 315, 355 and 400:

External rotor motor, IP44, Class F, thermal protection, working temperature from -40°C to $+70^{\circ}\text{C}$.

Models 450, 500, 560 and 630: IP65, Class F, thermal protection, working temperature from -40°C to $+70^{\circ}\text{C}$.

Models 4/710 and 800: IP55, Class F, working temperature from -40°C to $+70^{\circ}\text{C}$.

All motors are speed controllable by autotransformer except models /4-560H, /4-630, 710 and T/800.

Three phase motors are speed controllable by inverter.

Electrical supplies:

Single phase 230V-50Hz.

(Capacitor located inside the wiring terminal box).

Three phase 230/400V-50Hz or 400V-50Hz.



NEXT DAY
delivery*




Configuration for models /4-710 and 800.




Configuration for models 250, 315, 355 and 400.

Standard airflow direction: Form B (impeller over motor)


MOUNTING ACCESSORIES



DIMENSIONS (mm)




Models 250, 315, 355 and 400



Models 450, 500, 560 and 630

Model	Ø A	Ø B	C	Ø D	Ø E	Number of holes N
250	327	292	170	254	10	4
315	386	355	170	315	10	8
355	426	395	170	355	10	8
400	487	450	210	400	12	8
450	537	500	180	450	12	8
500	595	560	180	500	12	12
560	655	620	240	560	12	12
630	725	690	240	630	12	12



Model	Ø A	B	C	Ø D	E
					4 poles
710/L (4 poles)	806	770	380	710	415
710/H (4 poles)	806	770	380	710	444
800/L	896	860	380	800	437
800/K	896	860	380	800	448
800/G	896	860	380	800	447 (5,5kW) 515 (7,5kW)
800/H	896	860	380	800	515

TECHNICAL CHARACTERISTICS

Model	Speed (r.p.m.)	Maximum absorbed power (W)	Maximum current (A)		Sound pressure level @3m (dB(A))	Max. air volume (m³/h)	Weight (kg)	Speed controller		Variable frequency inverter	
			230 V	400 V				ELECTRONIC	AUTO- TRANSFORMER	S&P VFD*	
SINGLE PHASE 4 POLE											
TCBB/4-250/H	1430	44	0,2	-	42	900	8	REB-1	REV-3N		
TCBB/4-315/H	1435	105	0,6	-	52	1.990	11	REB-1	REV-3N		
TCBB/4-355/H	1420	120	0,6	-	52	2.462	13,2	REB-1	REV-3N		
TCBB/4-400/H	1420	360	1,6	-	60	5.190	15,5	REB-3	REV-5N		
TCBB/4-450/H	1410	594	2,6	-	63	6.810	21	REB-5	REV-5N		
TCBB/4-500/H	1410	636	2,8	-	66	7.500	25	REB-5	REV-5N		
TCBB/4-560/L	1405	1289	6	-	68	11.970	33	REB-6	REV-7N		
TCBB/4-560/H	1390	1461	6,6	-	69	12.960	34,7	-			
TCBB/4-630/L	1365	1707	7,5	-	70	15.730	40	-			

THREE PHASE 4 POLE

TCBT/4-250/H	1470	42	0,3	0,2	42	900	8	-	-	S&P VFD-M10A	S&P VFD-T 5A
TCBT/4-315/H	1445	99	0,5	0,3	51	1.950	11	-	-	S&P VFD-M10A	S&P VFD-T 5A
TCBT/4-355/H	1415	117	0,5	0,3	52	2.470	13,2	-	-	S&P VFD-M10A	S&P VFD-T 5A
TCBT/4-400/H	1410	268	1,0	0,6	60	4.950	15,5	-	-	S&P VFD-M10A	S&P VFD-T 5A
TCBT/4-450/H	1405	526	1,9	1,1	63	6.650	21	-	-	S&P VFD-M10A	S&P VFD-T 5A
TCBT/4-500/H	1420	641	2,6	1,5	66	7.590	25	-	-	S&P VFD-M10A	S&P VFD-T 5A
TCBT/4-560/L	1415	1184	3,8	2,2	68	12.090	33	-	-	S&P VFD-M10A	S&P VFD-T 5A
TCBT/4-560/H	1390	1348	4,2	2,4	69	13.370	34,7	-	-	S&P VFD-M10A	S&P VFD-T 5A
TCBT/4-630/L	1410	1770	5,9	3,4	70	16.060	39	-	-	S&P VFD-M10A	S&P VFD-T 5A
TCBT/4-630/H	1400	1940	6,2	3,6	70	17.030	40	-	-	S&P VFD-M10A	S&P VFD-T 5A
TCBT/4-710/L	1435	2175	6,4	3,7	73	20.290	46	-	-	S&P VFD-M10A	S&P VFD-T 5A
TCBT/4-710/H	1460	3441	10,6	6,1	73	26.420	54	-	-	S&P VFD-M16A	S&P VFD-T 9A
TCBT/4-800/L	1460	3750	11,3	6,5	76	29.950	65	-	-	S&P VFD-M16A	S&P VFD-T 9A
TCBT/4-800/K	1460	5177	-	8,8	76	34.950	68	-	-	-	S&P VFD-T 13A
TCBT/4-800/G	1470	6146	-	11,1	77	40.040	81	-	-	-	S&P VFD-T 13A
TCBT/4-800/H	1475	7688	-	13	78	42.490	89	-	-	-	S&P VFD-T 17A

* Inverter control: VFD-M - 1-Phase 230V Input, 3-Phase 400V Output.

VFD-T - 3-Phase 400V Input, 3-Phase 400V Output.


TCBB/T AXIAL CASED FAN PERFORMANCE DATA

Airflow m³/s @ Static Pressure Pa

Model	0	25	50	75	100	125	150	175	200	250	300	350	400
SINGLE PHASE 4 POLE													
TCBB/4-250/H	0.249	0.176											
TCBB/4-315/H	0.553	0.501	0.425										
TCBB/4-355/H	0.684	0.623	0.554	0.324									
TCBB/4-400/H	1.402	1.312	1.218	0.980									
TCBB/4-450/H	1.928	1.864	1.782	1.618	1.512	1.425							
TCBB/4-500/H	2.084	2.015	1.942	1.860	1.762	1.633	1.465						
TCBB/4-560/L	3.325	3.241	3.154	3.060	2.954	2.829	2.671	2.474	2.249				
TCBB/4-560/H	3.384	3.298	3.211	3.121	3.027	2.920	2.777	2.558					
TCBB/4-630/L	4.439	4.322	4.203	4.080	3.951	3.808	3.646	3.460	3.247				
THREE PHASE 4 POLE													
TCBT/4-250/H	0.248	0.136											
TCBT/4-315/H	0.540	0.507	0.459										
TCBT/4-355/H	0.686	0.622	0.538										
TCBT/4-400/H	1.376	1.276	1.181	0.976									
TCBT/4-450/H	1.848	1.763	1.674	1.575	1.462	1.330							
TCBT/4-500/H	2.108	2.037	1.964	1.884	1.795	1.686	1.539						
TCBT/4-560/L	3.359	3.272	3.180	3.083	2.971	2.837	2.663	2.451	2.192				
TCBT/4-560/H	3.714	3.616	3.515	3.403	3.265	3.080	2.838	2.603					
TCBT/4-630/L	4.547	4.431	4.312	4.187	4.053	3.904	3.739	3.557	3.363	2.819			
TCBT/4-630/H	4.731	4.627	4.519	4.406	4.281	4.136	3.959	3.733	3.492	3.052			
TCBT/4-710/L (1,5kW)	5.636	5.493	5.349	5.206	5.064	4.921	4.776	4.628	4.469	4.052	3.030		
TCBT/4-710/H (3kW)	7.338	7.193	7.047	6.898	6.743	6.580	6.406	6.220	6.018	5.587	5.170		
TCBT/4-800/L (3kW)	8.319	8.170	8.020	7.868	7.712	7.550	7.380	7.200	7.005	6.544	5.926	4.634	
TCBT/4-800/K (4kW)	9.708	9.549	9.390	9.228	9.064	8.895	8.719	8.536	8.343	7.912	7.364	6.363	
TCBT/4-800/G (5,5kW)	10.695	10.496	10.297	10.095	9.889	9.679	9.461	9.236	9.000	8.493	7.939	7.266	
TCBT/4-800/H (7,5kW)	11.804	11.587	11.371	11.154	10.937	10.719	10.501	10.283	10.066	9.630	9.162	8.540	

LONGAR® Type 4

Mesh Filter



LONGAR® TYPE 4 FEATURES:

- The LONGAR® Type 4 Mesh filter is manufactured using a patented expanded mesh, this offers a unique design based on many years of R&D. This results in a mesh that delivers greater air or grease arrestance, integral strength and low pressure loss.
- Comes with a safety edge channel to offer greater strength and safety over conventional products available on the market place.
- Using an Expanded metal multi-layer pad we are able to offer a panel with greater rigidity and importantly the pad cannot migrate particles, which can be found in 'knit mesh' filters, these types of panels can be hazardous where strands can break away from the filter.
- Due to the nature of the material that we use, its integral strength means when it comes to cleaning it will stand up well, and outlast panels of lesser constructions.
- Tested to Eurovent 4/5.
- Handles and drain holes are available.
- Available in Galvanised Steel, Stainless Steel and Aluminium.

APPLICATIONS

- Primary air filtration G2/G3
- Kitchens
- Cooker hoods
- All types of grease extraction
- General heating and ventilation pre-filtration

LONGAR® TYPE 4 MESH FILTER

The LONGAR® Type 4 Mesh filter is the result of years of experience in the manufacture and development of filters for the HEVAC world. With over 40 years of manufacturing experience the products brought to the market place today are clearly world class in price and product.

The LONGAR® Type 4 is a superior grease filter, available in a large selection of sizes and materials options.

Our Mesh filters are of robust construction and are used for a variety of applications, grease and air or dust collection applications, coalescer and spark arrestance, ideal as a prefilter for large particle contaminants and widely used in high air volume applications.

CONSTRUCTION DETAILS / MATERIAL SPECIFICATION

Media: Expanded metal patented design to aid filtration, available in stainless steel, galvanised steel, and aluminium.

Frame: U shaped section supplied with safety edge, available in stainless steel, galvanised steel and aluminium.

Filter thickness: Filter panels are available in actual thicknesses of: 8,10,12,20,25,40,45,50 and 95mm. Other sizes available on request.

Support mesh: Our own Q14 mesh is used in the grease filter as the support mesh.

Handles and drain holes: Folding handles and drain holes can be supplied as an option when required. They are fitted by default to the short dimension, unless otherwise stated by the customer at the time of ordering.

Housings: We can supply front withdrawal housings where required, see separate data sheet.

For technical specifications, part numbers and ordering information, please see overleaf.

LONGAR® Type 4

Mesh Filter

FITTING INSTRUCTIONS

- Fit products, handles in direction of air in.
- Product vertical in air stream.
- Drain holes lower edge to exit into drip tray if installed.

HANDLING

- Handle with care when unpacking.
- Store in dry and frost protected place.

MAINTENANCE

- All maintenance should be carried out in accordance with the planned maintenance set by installation contractor.
- When handling any components suitable PPE should be used - gloves, eye protection and access equipment.
- Filters should be cleaned by a trained operative either daily for heavy use or weekly for light use.
- For more exact guide to cleaning you should contact a cleaning specialist.

PACKAGING

All units are packaged in double wall boxes with separators for standard sizes, glued closed for protection whilst in transit against contamination.

TECHNICAL SPECIFICATIONS

Tested to Eurovent 4/5

Fire rating = UL Class 2

100% relative humidity

Longar specifies the Grease Filter as height x width x thickness. The handles are fixed to the height and drain holes punched on the width. Please ensure correct orientation is given when ordering.

SIZE ORDERING GUIDE (TOLERANCES +/- 2mm)			
Part Number	Actual Size HxWxD	Nominal Size HxWxD	Weight
ALIGLV49524145	241 x 495 x 45mm	254 x 508 x 50mm	1.58kgs
	9.49 x 19.49 x 1.77"	10 x 20 x 2"	3.48lbs
ALIGLV39439445	394 x 394 x 45mm	406 x 406 x 50mm	1.90kgs
	15.51 x 15.51 x 1.77"	16 x 16 x 2"	4.18lbs
ALIGLV49539445	394 x 495 x 45mm	406 x 508 x 50mm	2.39kgs
	15.51 x 19.49 x 1.77"	16 x 20 x 2"	5.26lbs
ALIGLV44444445	444 x 444 x 45mm	457 x 457 x 50mm	2.43kgs
	17.48 x 17.48 x 1.77"	18 x 18 x 2"	5.35lbs
ALIGLV49549545	495 x 495 x 45mm	508 x 508 x 50mm	2.92kgs
	19.49 x 19.49 x 1.77"	20 x 20 x 2"	6.42lbs
ALIGLV59759745	597 x 597 x 45mm	609 x 609 x 50mm	3.90kgs
	23.50 x 23.50 x 1.77"	24 x 24 x 2"	8.58lbs
FINAL RECOMMENDED PRESSURE DROP: 200 PASCALS			

Pressure drop and airflow information available on request.



LONGAR INDUSTRIES

FILTERS AND FABRICATIONS FOR A CLEANER ENVIRONMENT

Longar Industries Limited, Unit 25, Glenmore Business Park, Colebrook Way Weyhill Road, Andover, Hampshire SP10 3GZ United Kingdom

T +44 (0)1264 332 993 F +44 (0)1264 332 994 E info@longarind.com W www.longarind.com

As part of our program for continuous improvement, Longar Ltd reserves the right to change specifications without notice. 15-01-2016.

LONGAR® Type II

Pleated Panel Filters



LONGAR® TYPE II FEATURES:

- Moisture resistant cardboard frame.
- G4 efficiency to provide a good base level of filtration.
- Fully supported media bonded to expanded mesh grid.
- The filtering media is bonded to the case to eliminate air by-pass.
- Strong, robust construction.
- Extended surface area.
- High dust holding capacity.
- Dimensions of product are part marked into frame for positive ID.

APPLICATIONS

- Hotels
- Offices
- Food production
- Air conditioning
- Hospitals
- Pre-filtration asbestos removal

LONGAR® TYPE II PLEATED PANEL FILTER

Used in a variety of HEVAC applications where higher level air cleanliness is needed over the standard pre filters. Glass media is unacceptable in food and pharmaceutical industries and in some hospital areas. Especially useful where the installation requires a combination of high arrestance coupled with control over smaller particles. The high capacity version is selected when space is at a premium; filter sizes match the rated capacities of bag filters.

CONSTRUCTION / MATERIAL SPECIFICATIONS

The LONGAR® Type II is manufactured with pleated synthetic media, and an expanded diamond grid with 97% open area. The casing is constructed from a heavy duty rigid water resistant card, with support members along the diagonals. The media is bonded to the support grid and the frame in order to avoid the possibility of air bypass. The case is designed for minimum resistance and maximum free area, the case is also crease formed to stop moisture ingress. The product can be manufactured in a variety of depths from 22mm to 97mm deep. Optional metal frame available as shown above.

22mm (1") Filters are 9 Pleats per 300mm (1ft)
47mm (2") Filters are 9 Pleats per 300mm (1ft)
97mm (4") Filters are 9 Pleats per 300mm (1ft)

TYPE II HIGH CAPACITY PLEATED PANEL

We are able to manufacture the Type II with increased filter media over the standard product, for situations where an increase in air volume is required.

22mm (1") Filters are 12 Pleats per 300mm (1ft)
47mm (2") Filters are 12 Pleats per 300mm (1ft)
97mm (4") Filters are 12 Pleats per 300mm (1ft)

TYPE II HIGH EFFICIENCY PLEATED PANEL

Where situations arise we manufacture the Type II with a higher grade of filter media, F6, F7, F8 are available.

LONGAR® TYPE II IMPREGNATED CARBON PLEATED PANELS

For less demanding situations the use of impregnated media can be considered. They utilise non-woven synthetic media, which is then impregnated with activated carbon. They offer an alternative to our granular carbon systems however they cannot offer either the life span or dwell time that can be found with the rest of the range.

For technical specifications, part numbers and ordering information, please see overleaf.

LONGAR® Type II

Pleated Panel Filters

FITTING INSTRUCTIONS

- Fit products, observe direction of airflow indicator

HANDLING

- Handle with care when unpacking.
- Store in dry and frost protected place.

MAINTENANCE

- All maintenance and replacement schedules will be set by the original equipment installer. Please refer to this for more information.
- When handling any components suitable PPE should be used – gloves, eye protection and access equipment should be used where required.
- Filters should not be cleaned but replaced when required in accordance with maintenance schedule set by the installation contractor.

PACKAGING

All units are packaged in double wall boxes, glued closed for protection whilst in transit against contamination.

TECHNICAL SPECIFICATIONS

SIZE ORDERING GUIDE (TOLERANCES +/- 2mm)				
Part Number	Actual Size HxWxD	Nominal Size HxWxD	Weight	Available Efficiencies *
PPF24824822	248 x 248 x 22mm	254 x 254 x 25mm	0.07kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	9.76 x 9.76 x 0.87"	10 x 10 x 1"	0.15lbs	
PPF49624822	496 x 248 x 22mm	508 x 254 x 25mm	0.14kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.53 x 9.76 x 0.87"	20 x 10 x 1"	0.31lbs	
PPF29329322	293 x 293 x 22mm	304 x 304 x 25mm	0.09kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	11.54 x 11.54 x 0.87"	12 x 12 x 1"	0.21lbs	
PPF59429422	594 x 294 x 22mm	609 x 304 x 25mm	0.19kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	23.39 x 11.57 x 0.87"	24 x 12 x 1"	0.41lbs	
PPF37537522	375 x 375 x 22mm	381 x 381 x 25mm	0.15kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	14.76 x 14.76 x 0.87"	15 x 15 x 1"	0.34lbs	
PPF49637522	496 x 375 x 22mm	508 x 381 x 25mm	0.19kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.53 x 14.76 x 0.87"	20 x 15 x 1"	0.41lbs	
PPF49639622	496 x 396 x 22mm	508 x 406 x 25mm	0.20kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.53 x 15.59 x 0.87"	20 x 16 x 1"	0.43lbs	
PPF62039622	620 x 396 x 22mm	635 x 406 x 25mm	0.24kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	24.41 x 15.59 x 0.87"	25 x 16 x 1"	0.53lbs	
PPF44844822	448 x 448 x 22mm	457 x 457 x 25mm	0.19kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	17.64 x 17.64 x 0.87"	18 x 18 x 1"	0.42lbs	
PPF49649622	496 x 496 x 22mm	508 x 508 x 25mm	0.24kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.53 x 19.53 x 0.87"	20 x 20 x 1"	0.52lbs	
PPF59649622	596 x 496 x 22mm	609 x 508 x 25mm	0.27kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	23.46 x 19.53 x 0.87"	24 x 20 x 1"	0.60lbs	
PPF62049622	620 x 496 x 22mm	635 x 508 x 25mm	0.28kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	24.41 x 19.53 x 0.87"	25 x 20 x 1"	0.63lbs	
PPF59659622	596 x 596 x 22mm	609 x 609 x 25mm	0.31kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	23.46 x 23.46 x 0.87"	24 x 24 x 1"	0.68lbs	
PPF24824847	248 x 248 x 47mm	254 x 254 x 50mm	0.12kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	9.76 x 9.76 x 1.85"	10 x 10 x 2"	0.26lbs	

Pressure drop and airflow information available on request.

LONGAR® Type II

Pleated Panel Filters

TECHNICAL SPECIFICATIONS

SIZE ORDERING GUIDE (TOLERANCES +/- 2mm)				
Part Number	Actual Size HxWxD	Nominal Size HxWxD	Weight	Available Efficiencies *
PPF49724347	497 x 243 x 47mm	508 x 254 x 50mm	0.21kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.57 x 9.57 x 1.85"	20 x 10 x 2"	0.45lbs	
PPF29329347	293 x 293 x 47mm	304 x 304 x 50mm	0.15kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	11.54 x 11.54 x 1.85"	12 x 12 x 2"	0.33lbs	
PPF59628947	596 x 289 x 47mm	609 x 304 x 50mm	0.28kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	23.46 x 11.38 x 1.85"	24 x 12 x 2"	0.61lbs	
PPF37237247	372 x 372 x 47mm	381 x 381 x 50mm	0.22kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	14.65 x 14.65 x 1.85"	15 x 15 x 2"	0.48lbs	
PPF39439447	394 x 394 x 47mm	406 x 406 x 50mm	0.25kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	15.51 x 15.51 x 1.85"	16 x 16 x 2"	0.54lbs	
PPF49637547	496 x 375 x 47mm	508 x 381 x 50mm	0.27kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.53 x 14.76 x 1.85"	20 x 15 x 2"	0.60lbs	
PPF49639647	496 x 396 x 47mm	508 x 406 x 50mm	0.29kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.53 x 15.59 x 1.85"	20 x 16 x 2"	0.63lbs	
PPF62039647	620 x 396 x 47mm	635 x 406 x 50mm	0.34kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	24.41 x 15.59 x 1.85"	25 x 16 x 2"	0.75lbs	
PPF44644647	446 x 446 x 47mm	457 x 457 x 50mm	0.28kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	17.56 x 17.56 x 1.85"	18 x 18 x 2"	0.61lbs	
PPF49649647	496 x 496 x 47mm	508 x 508 x 50mm	0.34kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.53 x 19.53 x 1.85"	20 x 20 x 2"	0.75lbs	
PPF59639647	596 x 396 x 47mm	609 x 406 x 50mm	0.33kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	23.46 x 15.59 x 1.85"	24 x 16 x 2"	0.73lbs	
PPF59649647	596 x 496 x 47mm	609 x 508 x 50mm	0.39kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	23.46 x 19.53 x 1.85"	24 x 20 x 2"	0.87lbs	
PPF62049647	620 x 496 x 47mm	635 x 508 x 50mm	0.39kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	24.41 x 19.53 x 1.85"	25 x 20 x 2"	0.87lbs	
PPF59659647	596 x 596 x 47mm	609 x 609 x 50mm	0.47kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	23.46 x 23.46 x 1.85"	24 x 24 x 2"	1.02lbs	
PPF24824897	248 x 248 x 97mm	254 x 254 x 102mm	0.22kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	9.76 x 9.76 x 3.82"	10 x 10 x 4"	0.49lbs	
PPF49624897	496 x 248 x 97mm	508 x 254 x 102mm	0.38kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.53 x 9.76 x 3.82"	20 x 10 x 4"	0.84lbs	
PPF29329397	293 x 293 x 97mm	304 x 304 x 102mm	0.28kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	11.54 x 11.54 x 3.82"	12 x 12 x 4"	0.61lbs	
PPF59728997	597 x 289 x 97mm	609 x 304 x 102mm	0.48kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	23.50 x 11.38 x 3.82"	24 x 12 x 4"	1.06lbs	

Pressure drop and airflow information available on request.

LONGAR® Type II

Pleated Panel Filters

TECHNICAL SPECIFICATIONS

SIZE ORDERING GUIDE (TOLERANCES +/- 2mm)				
Part Number	Actual Size HxWxD	Nominal Size HxWxD	Weight	Available Efficiencies *
PPF37537597	375 × 375 × 97mm	381 × 381 × 102mm	0.41kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	14.76 × 14.76 × 3.82"	15 × 15 × 4"	0.90lbs	
PPF39639697	396 × 396 × 97mm	406 × 406 × 102mm	0.44kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	15.59 × 15.59 × 3.82"	16 × 16 × 4"	0.97lbs	
PPF49637597	496 × 375 × 97mm	508 × 381 × 102mm	0.49kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.53 × 14.76 × 3.82"	20 × 15 × 4"	1.08lbs	
PPF49639697	496 × 396 × 97mm	508 × 406 × 102mm	0.52kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.53 × 15.59 × 3.82"	20 × 16 × 4"	1.15lbs	
PPF62039697	620 × 396 × 97mm	635 × 406 × 102mm	0.61kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	24.41 × 15.59 × 3.82"	25 × 16 × 4"	1.33lbs	
PPF44644697	446 × 446 × 97mm	457 × 457 × 102mm	0.52kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	17.56 × 17.56 × 3.82"	18 × 18 × 4"	1.14lbs	
PPF49649697	496 × 496 × 97mm	508 × 508 × 102mm	0.66kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	19.53 × 19.53 × 3.82"	20 × 20 × 4"	1.46lbs	
PPF59639697	596 × 396 × 97mm	609 × 406 × 102mm	0.59kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	23.46 × 15.59 × 3.82"	24 × 16 × 4"	1.29lbs	
PPF59649697	596 × 496 × 97mm	609 × 508 × 102mm	0.69kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	23.46 × 19.53 × 3.82"	24 × 20 × 4"	1.52lbs	
PPF62049697	620 × 496 × 97mm	635 × 508 × 102mm	0.71kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	24.41 × 19.53 × 3.82"	25 × 20 × 4"	1.56lbs	
PPF59659697	596 × 596 × 97mm	609 × 609 × 102mm	0.79kgs	G4, F6, F7, F8, High Capacity, Carbon Impregnated Pleated Panels
	23.46 × 23.46 × 3.82"	24 × 24 × 4"	1.74lbs	
FINAL RECOMMENDED PRESSURE LOSS: 250 PASCALS				

Pressure drop and airflow information available on request.

- *Efficiency required to be confirmed at a time of ordering.



LONGAR INDUSTRIES

FILTERS AND FABRICATIONS FOR A CLEANER ENVIRONMENT

Longar Industries Limited, Unit 25, Glenmore Business Park, Colebrook Way Weyhill Road, Andover, Hampshire SP10 3GZ United Kingdom

T +44 (0)1264 332 993 F +44 (0)1264 332 994 E info@longarind.com W www.longarind.com

As part of our program for continuous improvement, Longar Ltd reserves the right to change specifications without notice. 15-01-2016.

LONGAR® Type 3

Low Pressure Baffle Filter



*Stainless steel 240 grit finish - standard handles



*Stainless steel bright annealed finish - optional fixed high temp handles

LONGAR® TYPE 3 FEATURES:

- Low pressure loss
- Polished finish or 240 grit dull grain finish
- Fully welded construction – all stainless steel construction
- Robust construction, our strongest filter yet
- Folding handles and drain holes standard (optional rigid handle available)
- Meets HVCA DW172 requirements
- Stock Sizes 2-3 days delivery, custom sizes available
- Cutsafe safety edges

APPLICATIONS

- Commercial kitchens
- Water mist separation
- Spark arrestors
- Sand filtration

LONGAR® TYPE 3 BAFFLE FILTER

For use in commercial kitchens and ventilation to extract grease laden air and offer a barrier to flame. The Type 3 has been developed for customers that require a lower pressure baffle filter, it still holds many of the features of the premium Type 2 yet offer a lower resistance to air. The Type 3 is available in standard depths of 20mm and 45mm. Custom sizes available on request. Meets DW172 and ISO9001.

CONSTRUCTION / MATERIAL SPECIFICATION

As standard all baffles are manufactured with Stainless Steel 430 polished finish and 240 Grit Dull Grain Finish. Maximum Operating temperature 400C or 750F.

FITTING INSTRUCTIONS

- Fit products, handles in direction of air in.
- Product vertical in air stream.

HANDLING

- Handle with care when unpacking.
- Store in dry and frost protected place.

MAINTENANCE

- All maintenance should be carried out in accordance with the planned maintenance set by installation contractor.
- When handling any components suitable PPE should be used - gloves & eye protection and access equipment.
- Filters should be cleaned by a trained operative either daily for heavy use or weekly for light use.
- For more exact guide to cleaning you should contact a cleaning specialist.

PACKAGING

All units are packaged in double wall boxes with separators for standard sizes, glued closed for protection whilst in transit against contamination.

FILTER CLASSIFICATION:

- Filter Class G2.
- UL Class 2.

MANUFACTURED TO:

- DW172.
- ISO9001.

For technical specifications, part numbers and ordering information, please see overleaf.

LONGAR® Type 3

Low Pressure Baffle Filter

TECHNICAL SPECIFICATIONS

Longar specifies the baffle filter as height x width x thickness. The handles are fixed to the height and drain holes punched on the width. The length of the baffle blade is the height; please ensure correct orientation is given when ordering.

SIZE ORDERING GUIDE (TOLERANCES +/- 2mm)			
Part Number	Actual Size HxWxD	Nominal Size HxWxD	Weight
TYPE3ST10X20	243 x 496 x 45mm	254 x 508 x 50mm	1.47kgs
	9.57 x 19.53 x 1.77"	10 x 20 x 2"	3.23lbs
TYPE3ST12X20	295 x 496 x 45mm	304 x 508 x 50mm	1.79kgs
	11.61 x 19.53 x 1.77"	12 x 20 x 2"	3.94lbs
TYPE3ST16X16	395 x 395 x 45mm	406 x 406 x 50mm	1.90kgs
	15.55 x 15.55 x 1.77"	16 x 16 x 2"	4.18lbs
TYPE3ST16X20	395 x 496 x 45mm	406 x 508 x 50mm	2.39kgs
	15.55 x 19.53 x 1.77"	16 x 20 x 2"	5.26lbs
TYPE3ST18X18	444 x 444 x 45mm	457 x 457 x 50mm	2.42kgs
	17.48 x 17.48 x 1.77"	18 x 18 x 2"	5.32kgs
TYPE3ST20X16	496 x 395 x 45mm	508 x 406 x 50mm	2.39kgs
	19.53 x 15.55 x 1.77"	20 x 16 x 2"	5.26lbs
TYPE3ST20X20	496 x 496 x 45mm	508 x 508 x 50mm	2.87kgs
	19.53 x 19.53 x 1.77"	20 x 20 x 2"	6.31lbs
TYPE3ST24X24	597 x 597 x 45mm	609 x 609 x 50mm	4.35kgs
	23.50 x 23.50 x 1.77"	24 x 24 x 2"	9.57lbs
FINAL RECOMMENDED PRESSURE DROP: 400 PASCALS			




LONGAR INDUSTRIES

FILTERS AND FABRICATIONS FOR A CLEANER ENVIRONMENT


Longar Industries Limited, Unit 25, Glenmore Business Park, Colebrook Way Weyhill Road, Andover, Hampshire SP10 3GZ United Kingdom
 T +44 (0)1264 332 993 F +44 (0)1264 332 994 E info@longarind.com W www.longarind.com

As part of our program for continuous improvement, Longar Ltd reserves the right to change specifications without notice. 15-01-2016.

LONGAR® Type 3 - Low PD - Baffle Filter - 243x495x45mm




LONGAR® Type 3 - Low PD - Baffle Filter - 395x395x45mm




LONGAR INDUSTRIES

FILTERS AND FABRICATIONS FOR A CLEANER ENVIRONMENT

LONGAR® Type 3 - Low PD - Baffle Filter - 395x496x45mm



LONGAR® Type 3 - Low PD - Baffle Filters - 444x444x45mm



LONGAR INDUSTRIES


FILTERS AND FABRICATIONS FOR A CLEANER ENVIRONMENT

Longar Industries Limited, Unit 25, Glenmore Business Park, Colebrook Way Weyhill Road, Andover, Hampshire SP10 3GZ United Kingdom


T +44 (0)1264 332 993 F +44 (0)1264 332 994 E info@longarind.com W www.longarind.com

As part of our program for continuous improvement, Longar Ltd reserves the right to change specifications without notice. 15-01-2016.

LONGAR® Type 3 - Low PD - Baffle Filters - 496x496x45mm



LONGAR® Type 3 - Low PD - Baffle Filters - 597x597x45mm



LONGAR INDUSTRIES

FILTERS AND FABRICATIONS FOR A CLEANER ENVIRONMENT

Longar Industries Limited, Unit 25, Glenmore Business Park, Colebrook Way Weyhill Road, Andover, Hampshire SP10 3GZ United Kingdom

T +44 (0)1264 332 993 F +44 (0)1264 332 994 E info@longarind.com W www.longarind.com

As part of our program for continuous improvement, Longar Ltd reserves the right to change specifications without notice. 15-01-2016.

LONGAR® Type 8

Activated Carbon Filters



LONGAR® TYPE 8 FEATURES:

- High grade carbon / High carbon content / Low pressure loss
- Robust modular construction
- Carbon Unit or panel format / Standard and Custom sizes available
- CNC manufactured / Precision products every time

APPLICATIONS

- Reduction of Cooking Odours
- Removal of Kerosene Exhaust Fumes
- General Odour Reduction
- Neutralisation of Ammonia and its Derivatives
- Removal of Formaldehyde
- Removal of Airborne Pollutants and Contaminants
- Removal of Acid Gases (please enquire as to specific contaminant)

LONGAR® TYPE 8 ACTIVATED CARBON FILTERS

Activated carbon has for many years been used to remove airborne noxious fumes and gases. Its origins date back to the First World War, when gas masks were first filled with Activated carbon to remove chlorine gas. Today Longar produces a wide range of carbon filters to deal with a variety of air pollution scenarios.

There are many situations where carbon filtration is used to eliminate toxic or offensive odours, some of these are sewage works, hospitals, slaughterhouses, restaurant kitchens, airports, toilets, wash rooms, laboratories, and office blocks.

PRE FILTRATION

Carbon filters are designed to remove fumes and odours, they are not suitable for removing dust and fine particles. If left unprotected, the life of the carbon product is severely reduced. To protect the filters use the correct pre filtration. If you are unsure please enquire for further information.

LONGAR® TYPE 8 ACTIVATED CARBON PANELS

The Activated carbon panel are sealed into a galvanised steel frame; a scrim is then added to protect the carbon surface from dust contamination. Sealing the carbon panel stops any air by-pass; our panels are manufactured using CNC technology to ensure precision manufacture with exact tolerances.

Our panels are the strongest on the market place with a wide range of standard sizes available, custom sizes are also available on request.

LONGAR® TYPE 8 ACTIVATED CARBON UNITS (ACU)

For a modular approach to fume removal the ACU is the ideal solution. The ACU unit is manufactured from a number of carbon panels held in place by a CNC made corrosion proof metal casing. The carbon panels inside the units are 25mm thick, sealed into the frames using polymer which eliminates the possibility of any air by-pass around the carbon.

LONGAR® TYPE 8 CYLINDRICAL FILTER

These are constructed from perforated galvanised steel then formed into cylindrical cartridges containing high grade or impregnated carbon. The cylinders have a bayonette fit into the filter mounting plate.

All cylinders have a unique feature of having the option to replace any spent carbon and then refill with new replenished carbon.

For technical specifications, part numbers and ordering information, please see overleaf.

LONGAR® Type 8

Activated Carbon Filters

FITTING INSTRUCTIONS

- Fit products in accordance with installation contractor's specifications. Observe direction of airflow.

HANDLING

- Handle with care when unpacking.
- Store in dry and frost protected place.

MAINTENANCE

- Carbon filters cannot be cleaned upon reaching the end of their service life. They must be replaced.
- All maintenance and replacement schedules will be set by the original equipment installer. Please refer to this for more information.
- When handling any components suitable PPE should be used – gloves, eye protection and access equipment.
- Carbon filters may be recycled.

PACKAGING

All units are packaged in double wall boxes, stapled closed for protection whilst in transit against contamination.

TECHNICAL SPECIFICATIONS

SIZE ORDERING GUIDE (TOLERANCES +/- 2mm)					
Part Number	Actual Size HxWxD	Nominal Size HxWxD	Weight	Airflow M³/SEC @0.12 Contact	Pressure Loss - Pascals
CARBONCUBE242424	597 x 597 x 597mm	609 x 609 x 609mm	60.00kgs	1.00	97
	23.50 x 23.50 x 23.50"	24 x 24 x 24"	132.00lbs		
CARBONCUBE242418	597 x 597 x 450mm	609 x 609 x 457mm	44.00kgs	0.75	97
	23.50 x 23.50 x 17.72"	24 x 24 x 18"	96.80lbs		
CARBONCUBE241824	597 x 450 x 597mm	609 x 457 x 609mm	46kgs	0.75	97
	23.50 x 17.72 x 23.50"	24 x 18 x 24"	101.20lbs		
CARBONCUBE182424	450 x 597 x 597mm	457 x 609 x 609mm	46kgs	0.75	97
	17.72 x 23.50 x 23.50"	18 x 24 x 24"	101.20lbs		
CARBONCUBE242416	597 x 597 x 395mm	609 x 609 x 406mm	40.00kgs	0.67	97
	23.50 x 23.50 x 15.55"	24 x 24 x 16"	88.00lbs		
CARBONCUBE242412	597 x 597 x 292mm	609 x 609 x 305mm	33.00kgs	0.50	97
	23.50 x 23.50 x 11.50"	24 x 24 x 12"	72.60lbs		
CARBONCUBE241224	597 x 297 x 597mm	609 x 304 x 609mm	32.00kgs	0.50	97
	23.50 x 11.69 x 23.50"	24 x 12 x 24"	70.40lbs		
CARBONCUBE24824	597 x 197 x 597mm	609 x 203 x 609mm	19.00kgs	0.33	97
	23.50 x 7.76 x 23.50"	24 x 8 x 24"	41.80lbs		
CARBONCUBE202018	495 x 495 x 445mm	508 x 508 x 457mm	36kgs	0.52	97
	19.49 x 19.49 x 17.52"	20 x 20 x 18"	79.20lbs		
CARBONCUBE181818	450 x 450 x 450mm	457 x 457 x 457mm	28.00kgs	0.42	97
	17.72 x 17.72 x 17.72"	18 x 18 x 18"	61.60lbs		
FINAL RECOMMENDED PRESSURE DROP: 450 PASCALS					

Pressure drop and airflow information available on request.



LONGAR INDUSTRIES

FILTERS AND FABRICATIONS FOR A CLEANER ENVIRONMENT

Longar Industries Limited, Unit 25, Glenmore Business Park, Colebrook Way Weyhill Road, Andover, Hampshire SP10 3GZ United Kingdom
 T +44 (0)1264 332 993 F +44 (0)1264 332 994 E info@longarind.com W www.longarind.com

As part of our program for continuous improvement, Longar Ltd reserves the right to change specifications without notice. 15-01-2016.

LONGAR® Type 8

Activated Carbon Housing



LONGAR® TYPE 8 FEATURES:

- High grade carbon / High carbon content / Low pressure loss
- Robust modular construction
- Carbon Unit or panel format / Standard and Custom sizes available
- CNC manufactured / Precision products every time

APPLICATIONS

- Reduction of Cooking Odours
- Removal of Kerosene Exhaust Fumes
- General Odour Reduction
- Neutralisation of Ammonia and its Derivatives
- Removal of Formaldehyde
- Removal of Airborne Pollutants and Contaminants
- Removal of Acid Gases (please enquire as to specific contaminant)

LONGAR® TYPE 8 ACTIVATED CARBON FILTERS

Activated carbon has for many years been used to remove airborne noxious fumes and gases. Its origins date back to the First World War, when gas masks were first filled with activated carbon to remove chlorine gas. Today Longar produces a wide range of carbon filters to deal with a variety of air pollution scenarios.

There are many situations where carbon filtration is used to eliminate toxic or offensive odours, some of these are sewage works, hospitals, slaughterhouses, restaurant kitchens, airports, toilets, wash rooms, laboratories, and office blocks..

PRE FILTRATION

Carbon filters are designed to remove fumes and odours, they are not suitable for removing dust and fine particles. If left unprotected, the life of the carbon product is severely reduced. To protect the filters use the correct pre filtration. If you are unsure please enquire for further information.



LONGAR® TYPE 8 ACTIVATED CARBON PANELS

The activated carbon panels are sealed into a galvanised steel frame; a scrim is then added to protect the carbon surface from dust contamination. Sealing the carbon panel stops any air by-pass; our panels are manufactured using CNC technology to ensure precision manufacture with exact tolerances.

Our panels are the strongest on the market place with a wide range of standard sizes available, custom sizes are also available on request.

LONGAR® TYPE 8 ACTIVATED CARBON UNITS (ACU)

For a modular approach to fume removal the ACU is the ideal solution. The ACU unit is manufactured from a number of carbon panels held in place by a CNC made corrosion proof metal casing. The carbon panels inside the units are 25mm thick, sealed into the frames using polymer which eliminates the possibility of any air by-pass around the carbon.

LONGAR® TYPE 8 CYLINDRICAL FILTER

These are constructed from perforated galvanised steel then formed into cylindrical cartridges containing high grade or impregnated carbon. The cylinders have a bayonette fit into the filter mounting plate.

All cylinders have a unique feature of having the option to replace any spent carbon and then refill with new replenished carbon.

For technical specifications, part numbers and ordering information, please see overleaf.

LONGAR® Type 8

Activated Carbon Housing

FITTING INSTRUCTIONS

- Fit products in accordance with installation contractor's specifications. Observe direction of airflow.

HANDLING

- Handle with care when unpacking.
- Store in dry and frost protected place.

MAINTENANCE

- Carbon filters cannot be cleaned upon reaching the end of their service life. They must be replaced.
- All maintenance and replacement schedules will be set by the original equipment installer. Please refer to this for more information.
- When handling any components suitable PPE should be used – gloves, eye protection and access equipment.
- Carbon filters may be recycled.

PACKAGING

All units are packaged on pallets custom built. Goods are sealed to protect whilst in transit against contamination.

TECHNICAL SPECIFICATIONS

Housing Size (mm) HxWxD	Airflow (m3/sec)	Contact time (sec)	Total clean, pressure drop (Pascals)
675 x 365 x 1500	0.50	0.12	256
675 x 665 x 1350	0.75	0.12	256
675 x 665 x 1500	1.00	0.12	256
675 x 965 x 1500	1.25	0.12	256
675 x 1265 x 1350	1.50	0.12	256
675 x 1265 x 1500	2.00	0.12	256
675 x 1865 x 1350	2.25	0.12	256
675 x 1650 x 1500	2.50	0.12	256
1290 x 965 x 1500	3.00	0.12	256
1290 x 1265 x 1350	3.25	0.12	256
1290 x 1265 x 1500	4.00	0.12	256

Pressure drop and airflow information available on request.



LONGAR INDUSTRIES

FILTERS AND FABRICATIONS FOR A CLEANER ENVIRONMENT

Longar Industries Limited, Unit 25, Glenmore Business Park, Colebrook Way Weyhill Road, Andover, Hampshire SP10 3GZ United Kingdom

T +44 (0)1264 332 993 F +44 (0)1264 332 994 E info@longarind.com W www.longarind.com

As part of our program for continuous improvement, Longar Ltd reserves the right to change specifications without notice. 15-01-2016.

FSAF450B2DA Silencer 500/8

Item Number: 50119

Circular attenuator suitable for direct connection to cased axial fans
Construction comprises galvanised steel outer casing, end rings fitted with tapped inserts to suit the relevant fan drilling detail. Inner bore is manufactured from perforated galvanised steel spiral tube retaining a 45 kg /m³ density acoustic media with a surface particulate membrane.




Technical parameters

Dimensions and weights

Weight	28 kg
--------	-------

Dimension



A	B	C	D	E	Weight kg
900	600	8	M10	500	28

Acoustic

Frequency Hz	63	125	250	500	1K	2K	4K	8K
Insertion Loss dBW	4	6	11	19	21	21	19	20

N.B. Above figures only apply when silencer is bolted direct to the fan flange.

RSA 450/450/080 (F)

thickness 80mm, without Core

Item Number: [311355](#)

Silencer

silencer RSA(F) for use together with axial fans of AXC-Range. For effective noise suppress the silencer should be mounted directly before or after the fan. The silencers is supplied with a flange according Eurovent 1/2.




Technical parameters

Dimensions and weights

Weight

14.1 kg

Dimension



	$\varnothing I$	$\varnothing E$	$\varnothing F$	$A \times B$	L
RSA(F) 450/450	450	610	500	8 x M10	450

Acoustic

Noise suppression dB (mid-frequency Hz)

	125	250	500	1k	2k	4k	8k
RSA(F) 450/450	1	4	12	12	9	6	6
RSA(F) 450/675	1	6	17	17	13	9	8
RSA(F) 450/900	1	7	21	21	15	10	8

Acoustic data tested in accordance to ISO 7235
(test report number 9580180)

Documents

- [Overview_RSA.pdf](#)
- [2014-01_EC-DECLARATION OF CONFORMITY RSA DE-EN.PDF](#)

Roof hood

HF



Description

Ventilation hood for air exit above roof, suitable for both industrial and comfort ventilation. The air is ejected in an upwards-directed jet. This avoids contaminating the air in the vicinity of the hood, and soiling of the area around the hood. The ejection is so effective that you can install a fresh air inlet in the immediate vicinity of the hood, without any special precautions.

The hood is made of galvanised sheet steel, and can also be supplied in other materials such as stainless steel sheet 1.4301, stainless acid-resistant steel sheet 1.4404, aluzinc AZ185 and painted in various colours, to special order. It has a net over the opening and an internal rain funnel to collect rainwater and snow, which is drained out of the hood through a hose. The hose can withstand temperatures of between -45 and +65 °C.

The hood has a flange connection, which includes a mating flange.


To avoid damage to the net in the opening the hood is supplied with transport protection. This must be removed before the hood is taken into service.

The hood is delivered with three turnable lifting and anchoring wire-loops. A single wire-loop shall not be exposed for forces exceeding 1500 N.

Ordering example


Product code **HF**
Dimension $\varnothing d$ **630**

Dimensions



				Roof through con- nection TGR	
Ød nom	ØD mm	H mm	m kg	50 mm	100 mm
				Size	
400	685	905	11,1	5	6
500	855	1055	20,0	6	7
630	1075	1295	38,0	8	9
800	1360	1640	63,0	9	10
1000	1600	2110	89,1	11	12
1250	2020	2615	118	14	15

Technical data



Circular duct

SR



Description


Circular duct.

Ducts are always produced locally and can therefore have different thicknesses and other specifications per country.

The ducts can be produced both with and without click function (notches).

Please specify when ordering.

Dimensions



Ød std nom	O πd m	A $\pi d^2/4$ m ²	t std [mm]	l std [mm]	ml std kg/m
63	0,198	0,003	0,5	3000	0,89
80	0,251	0,005	0,45	3000	0,91
100	0,314	0,008	0,45	3000	1,14
112	0,352	0,010	0,5	3000	1,42
125	0,393	0,012	0,45	3000	1,41
140	0,440	0,015	0,5	3000	1,76
150	0,471	0,018	0,5	3000	1,89
160	0,503	0,020	0,5	3000	2,02
180	0,565	0,025	0,5	3000	2,26
200	0,628	0,031	0,5	3000	2,56
224	0,704	0,039	0,6	3000	3,42
250 *	0,785	0,049	0,5	3000	3,18
280	0,880	0,062	0,55	3000	3,92
300 *	0,942	0,071	0,55	3000	4,20
315 *	0,990	0,078	0,55	3000	4,41
355 *	1,115	0,099	0,55	3000	4,96
400 *	1,257	0,126	0,55	3000	6,01
450 *	1,414	0,159	0,7	3000	8,60
500 *	1,571	0,196	0,7	3000	9,54
560 *	1,759	0,246	0,8	3000	12,2
600 *	1,885	0,283	0,7	3000	13,1
630 *	1,979	0,312	0,7	3000	12,0
710 *	2,231	0,396	0,8	3000	15,5
800 *	2,513	0,503	0,8	3000	17,4
900 *	2,827	0,636	0,9	3000	21,7
1000 *	3,142	0,785	0,9	3000	24,1
1120 *	3,519	0,985	0,9	3000	27,0
1250 *	3,927	1,227	0,9	3000	30,2
1400 *	4,398	1,539	1,25	2400	48,0
1500 *	4,712	1,767	1,25	2400	51,4
1600 *	5,027	2,011	1,25	2400	54,8

* With outturned stiffening corrugation.


Ordering example

	SR	200	3000	CLIC
Product				
Dimension Ød				
Length l				
Type				

Circular duct

SR

Technical data



Special versions

We can supply ducts with the following special designs:

- In intermediate dimensions, see page 15.
- Extra tight, with nitrile rubber seal in the lock seam
- In other sheet metal thicknesses

Extra tight, with seam seal

When extremely good sealing is required in the spiral seam, the ducts can also be supplied with a special rubber seal in the seam.

This seal is very effective at stopping leakage of vegetable oils and greases, and most petroleum products including white spirit.

Other sheet metal thicknesses

If extra stability is needed in ducts, because of high negative pressure etc., they can be supplied with thicker sheet metal than standard. Remember that the thickness increase always reduces the inner diameter. Fittings for such special ducts must be specified separately and sometimes have to be made specially.

Reinforcement corrugations

Ducts of $\phi 250$ mm and above are normally given stiffening corrugations to increase radial stiffness.



Circular duct

SR

Technical data

Strength

Positive pressure

In case of high positive pressure, the seal moulding lips will first start to whistle. At considerably higher pressure, the joints between the ducts will be forced apart. If you manage to fix the connections very well, the ducts will burst at their seams at even higher pressure. The high pressures needed for this to happen are not relevant to ventilation installations.

Negative pressure


In installations with high negative pressure, there is a risk that the ducts could collapse.

This phenomenon is referred to as buckling, and can suddenly happen at the weakest point in the system. Buckling wanders along the duct, which can be completely flattened. The weakest point is frequently a "transport dent" on a duct. For this reason, only use undamaged ducts in systems which are close to the critical pressure!

Strength and leakage

The performance of the gasket ability for tightness is different from the pressure limits and is shown in the table below.

In exceptional cases, additional strong ducts and fittings are needed. Lindab has developed a system that can withstand down to 5000 Pascal's negative pressure. To minimize costs and to be sure of the performance of the specific system, contact Lindab for precise dimensioning.



	Min Dim [nom]	Max Dim [nom]	Max Negative pressure [Pa]	Min Positive pressure [Pa]
Safe Gasket stability	63	1600	-5000	3000
Duct system Eurovent certified	63	315	-5000	2000
Duct system Eurovent certified	400	1250	-750	2000
Duct system according to EN 12237	63	1250	-750	2000
Duct system - Strong solution on request	63	1600	-5000	3000

Product Data Sheet



Product Code:

Issue No.

Issue Date:

Issue by:

TC103-60

A

03.10.09

D.B.P

Description

Light Duty Cantilever Arm Support - 600mm

Features




Brackets are designed to comply with BS6946

Manufactured from 6mm thick steel

Special Finish: All channel brackets are post hot dipped galvanised to BS729

General Characteristics


Material	Low carbon steel strip (BSEN10142:2000)
Finish	Hot Dipped Zinc
Cantilever Arm	41 x 41mm strut 2.5mm channel
Cantilever length	600mm
Suitable for Tray width	450mm




Recommended Safe Loads (kg)

x (m)	Total Uniformly Distributed Load (kg)	Concentrated Load (kg)
0.10	684	342
0.15	608	342
0.20	542	283
0.25	452	226
0.30	377	188
0.35	323	162
0.40	283	141
0.45	251	126
0.50	226	113
0.55	206	103
0.60	188	94
0.65	174	87
0.70	162	81
0.75	151	75

Dimensions





Anti Vibration Mounts (AV's)

Introduction

Anti-vibration mounting kits are available in both rubber and spring type, the correct selection and type employed will depend on the accurate calculation of the weight of the assembly to be supported.

Installation

AV mounts should not be fitted to a fan/silencer assembly unless there are flexible connectors fitted between the assembly and associated duct work.

AV mounts should be installed with the matched mounting feet and positioned such that they carry an equal proportion of the assembly weight. This is particularly important where fans and silencers are installed on suspension rods.

Figure 1. NAV 1 to NAV 5 (Resilient Rubber)




Figure 2. NAV 6 (Resilient Rubber)





Figure 3. NAV 49 to NAV 58 (Spring)



AV mounts are maintenance free but a periodical inspection is recommended to check security of fixings and condition of rubbers and springs.

Resilient Mounting Details

Figure 4.

NAV 1 to NAV 5 shown in floor (Figure 4) and suspended configurations (Figure 5).

Fans using size NAV 6 upwards require supporting steelwork to be designed (by others) for suspended applications.





Figure 5.



AV mounts isolate the fan only. Silencers/backdraught dampers and other "significant mass" accessories should form part of the fixed ductwork after the flexible connection.

Dimensions (mm) and Weights

Rubber Type

Code	A	B	Max. kg per kit
NAV1	30	50	20
NAV2	40	75	80
NAV3	40	75	180
NAV4	40	75	260
NAV5	40	75	130
NAV6	50	100	320

Spring Type

NAV49	77	76	400
NAV50	77	76	480
NAV51	77	76	520
NAV52	87	127	600
NAV53	87	127	700
NAV54	87	127	800
NAV55	87	127	950
NAV56	87	127	1110
NAV57	87	127	1270
NAV58	87	127	1430



Nuaire Limited Western Industrial Estate Caerphilly United Kingdom CF83 1NA
Telephone: 029 2088 5911 Facsimile: 029 2088 7033
Email: info@nuaire.co.uk www.nuaire.co.uk

Leaflet Number 671224 October 2004



Stainless Steel Fabrication

Commercial Kitchen Design and Installation

System Maintenance

It is important that the system is well maintained in order to operate a system that is functional on providing a high level of performance.

Maintenance requirements will vary, subject to the intensity of use and type of cooking. Therefore, frequency of cleaning and filter replacement will be adjusted to suit. The Tenant will ensure the following minimum levels of maintenance are adhered to.

The most advanced filtration systems and ductwork designs will quickly become completely ineffective at mitigating grease, smoke and odour, when the detailed maintenance regime is not followed the table below provides requirements for the type and frequency of maintenance in accordance with EMAQ guidelines.

We would recommend the following in accordance with BESA TR19 guidance guidelines on cleaning and maintenance.

Cleaning of ductwork – 1 month Heavy use 3 months Medium use and every 6 months light use.

Canopy on each session before or after session

G4 filters every 3 weeks or if system seems to have reduced suction/ performance (Extract & Supply) **if installed**

Cleaning baffle filters – after each service

Carbon filters – 3 months heavy use 6 months medium use 8 month light use. **If Installed**

Extract— 1 Month heavy used 3 Months moderate use 6 Months light use.

Extract full services – 12 months. For your insurance this is required

ESP Filter changing/cleaning – 3 months heavy use 6 months medium use 8 months light use. **If Installed**



Stainless Steel Fabrication
Commercial Kitchen Design and Installation

Unit5 Firefly Square Plantation Road Burscough Industrial Estate L40 8JT

VAT No. 245073616

Tel: 01704-893945 Fax: 0844-4122296

Email: fusionhot1@gmail.com Web: www.FusionHot.co.uk

Stainless Steel Fabrication

Commercial Kitchen Design and Installation

Kitchen extract component	Recommended maintenance intensity
Grease Smoke and Solid Filtration	
Grease filter – mesh/baffle/cartridge/water wash	Daily cleaning
Canopy UV	Quarterly clean replace lamps after 8000 hours of operation
Cold water mist hood	Daily cleaning
Electrostatic Precipitation	Clean every 4 weeks
Low intensity odour control	
3 stage fine filters	Replacement every 2 weeks or replace when system is reduced performance
Odour control	
UV odour control	Clean every 4 weeks annual lamp replacement
Ozone Injection unit	self-sufficient no need to clean
Ozone generation unit	No need to clean out of airstream
Adsorption activated carbon filter	3 to 5 months filter replacement of when system has reduced performance

Usage	Frying time	Minimum clean frequency
Heavy Use	12-16 hours per day	3 Monthly
Moderate use	6-12 hours per day	6 Monthly
Low Use	2-6 hours per	12 Monthly

All duct work should be cleaned by a qualified tr19 person, who should issue a certificate after cleaning, this is important for your insurance.

Please note these are only guidelines as all systems are designed differently

TERMS AND CONDITIONS

By ordering the goods you agree to be bound by our terms and conditions below and recognise the services/products we have not included in our quotation for you unless otherwise stated.

- Ventilation system to EMAQ Guidelines (subject to further quotation).
- Odour control.
- Noise management.
- Fire rated ductwork.
- Fire rated insulation.
- Fire rating of walls that ductwork passes through.
- Planning permission (client's responsibility – work will not start without sufficient authority approval).
- Hanging of canopies over 4500mm from FFL.
- Infill panels to make good between the top of the canopy and ceiling.
- Masking gaps that occur during canopy installation due to inaccuracies in the building structure.
- Any specialist fixings to suit building structure.
- Balancing and commissioning of canopies.
- All electrical works.
- Final electrical connections and controls commissioning.
- Gas works including gas valve (interlock).
- Pipe work and inclusion of valves.
- Builders works and weather proofing of openings (scaffolding or lifting equipment).
- Structural works to roof area.
- Protection to flooring internal.
- Lifting of plant to roof level / scaffolding.
- Edge protection.
- Thermal insulation.
- Boarding to ceiling void areas.
- Canopy protection on completion of installation.
- Fire suppression.
- Strip out / Removal of existing canopies / ductwork.
- Any items not specifically itemized within your quotation are excluded.
- Earth bonding.
- Out of hours working (Normal working hours being Mon-Fri 8.30-5.30pm excluding bank holidays, hours include travelling time) any extra hours due to any unforeseen circumstances will be charged at £50ph payable direct to fitters.
- Notifications to local authorities, building, planning, fire etc.
- Builders, joiners, scaffolding, electrical, plumbing, roofing works.
- Waterproofing of walls and roofs where ductwork terminates exits (roofer will be required to seal roofs).
- Ductwork insulation.
- Inspection hatches to TR19 to be installed by others.
- Extraction canopy fan/speed control wiring to mains/board.
- All new fans are covered under manufactures warranty if claiming for a fault a new fan must be purchased and the fan in question sent back to the manufacture for inspection at your cost, if fan is found at fault under warranty, they will reimburse the cost of the fan.
- Fan inspection and warranty call outs to inspect/replace fans are not covered, and labour costs paid by the client.
- Extraction fan / controller fail due to incorrect wiring, replacement parts to be paid by client and parts send back to manufacturer for inspection at clients cost.
- Heater battery for air input system.
- Provision of grease traps if required.
- Finding of asbestos all works must stop until made safe by others.
- Return visit to site due to services being incorrect or not live and enabled for commissioning, a chargeable site instruction. would be required for any visits beyond our control.
- We specifically exclude any works not mentioned.
- VAT.
- Once payment made any refund will be subject to a 25% restocking charge and fee incurred.
- The company (FUSIONHOT LTD) is suppliers. Fitting is carried out by a third-party company and is the customer's responsibility to check all relevant details of that company, any problems with the fitting is between the customer and the third-party company. All correspondence should be between these two and not FUSIONHOT LTD.