

Q40

Fencing

Fencing systems

170 3.5m & 1.8m High Acoustic Fence

1. Manufacturer: [Gramm Barrier Systems Ltd](#) or similar approved
 - 1.1. Contact details
 - 1.1.1. Address: 18 Clinton Place
Talland Parade
Seaford
East Sussex
BN25 1NP
 - 1.1.2. Telephone: +44 (0)1323 872243
 - 1.1.3. Web: <https://www.grammbarriers.com>
 - 1.1.4. Email: info@grammbarriers.com
 - 1.2. Product reference: [POLYSoundBlok Recycled Polymer Acoustic Barrier](#) or similar approved
 2. Posts: Polyester powder-coated (PPC) steel posts.
RAL 6005
 3. Post foundations: Concrete foundations.
 4. Rails: Not applicable.
 5. Base boards: Not applicable.
 6. Panels: POLYSoundBlok® panels, green.
 7. Fence topping: Manufacturer's standard.
 8. Site applied finishes: Not applicable.
 9. Panel size: 2m Wide x 3.5m Height & 2m Wide x 1.8m Height
 10. Fixings: Consult Manufacturer
 11. Technical characteristics, other: Barrier rating: A5, B3. Absorption: 16 DLa. Reflection: 28 DLr.
 12. Panel weight: 23 kg/m².
-



430 Weldmesh Sports Fence

1. Manufacturer: [Zaun Limited](#) or similar approved
 - 1.1. Contact details
 - 1.1.1. Address: Steel Drive
Wolverhampton
West Midlands
United Kingdom
WV10 9ED
 - 1.1.2. Telephone: [+44 \(0\)1902 796699](tel:+44(0)1902796699)
 - 1.1.3. Web: <https://www.zaun.co.uk>
 - 1.1.4. Email: sales@zaun.co.uk
 - 1.2. Product reference: [Super Rebound MUGA Sports Fencing](#) or similar approved
2. Standard: To BS 1722-14, ISO 12944.
3. Posts: 100 x 50 mm rectangular hollow section (RHS) posts.
4. Panels: Super Rebound 8 mesh.
5. System accessories: Pedestrian gate. Vehicular gate.
6. Height: 3m above ground
7. Applied finish: Galvanized and polyester powder coated.
RAL 6005
8. Gates: 50 x 50 mm RHS frame with Zaun Super 6 Rebound mesh welded inside the frame, slide latch, rubber bump stop, two gate posts.
9. Panel fixings: Panels fixed to posts with full height 40 x 5 mm clamp bar with bolt fixings at 200 mm centres with EPDM inserts.
10. Width: 2510 mm.
11. Mesh size: 66.6 x 50 mm at lower 1.2 m with 200 mm x 50mm above.
12. Fixings: Anti tamper security fixings.



Gates

570 Carbon steel gates - Double Leaf

1. Dimensions
 - 1.1. Span: 3000mm
 - 1.2. Height: 2000 mm.
2. Posts: Carbon steel.
3. Gate leaves: Super Rebound.
4. Hardware
 - 4.1. Securing: Slide bar.
5. Finish as delivered
 - 5.1. Applied finish: Galvanized and polyester powder-coated (PPC).
RAL 6005
6. Closers: Required.
7. Opening: Outwards.
8. Accessories/ Other requirements: Not required.
9. Manufacturer: [Zaun Limited](#) or similar and approved
10. Contact details
 - 10.1. Address: Steel Drive
Wolverhampton
West Midlands
United Kingdom
WV10 9ED
 - 10.2. Telephone: [+44 \(0\)1902 796699](tel:+44(0)1902796699)
 - 10.3. Web: <https://www.zaun.co.uk>
 - 10.4. Email: sales@zaun.co.uk
11. Manufacturer: Zaun Limited or similar and approved
 - 11.1. Product reference: [Pedestrian Gates \(Double leaf\)](#)



571 Carbon steel gates - Single Leaf

1. Dimensions
 - 1.1. Span: 1200mm
 - 1.2. Height: 2000 mm.
2. Posts: Carbon steel.
3. Gate leaves: Super Rebound.
4. Hardware
 - 4.1. Securing: Slide bar.
5. Finish as delivered
 - 5.1. Applied finish: Galvanized and polyester powder-coated (PPC).
RAL 6005
6. Closers: Required.
7. Opening: Outwards.
8. Accessories/ Other requirements: Not required.
9. Swing: Left hand.
10. Manufacturer: [Zaun Limited](#) or similar and approved
11. Contact details
 - 11.1. Address: Steel Drive
Wolverhampton
West Midlands
United Kingdom
WV10 9ED
 - 11.2. Telephone: [+44 \(0\)1902 796699](tel:+441902796699)
 - 11.3. Web: <https://www.zaun.co.uk>
 - 11.4. Email: sales@zaun.co.uk
12. Manufacturer: Zaun Limited or similar approved
 - 12.1. Product reference: [Pedestrian Gates \(Single leaf\)](#) or similar and approved

