

PRO-FORMA 1: Sustainable Drainage System: Planning Permission

This pro-forma is a requirement of the Planning Validation Checklist. You **must complete all white boxes in full** and submit this pro-forma along with your supporting evidence to the Local Planning Authority for any application which seeks planning permission for major development (as defined in section 2 of [Statutory Instrument 2015 No. 595](#)).

This pro-forma supports developers and regulators in **summarising and confirming** how surface water from a development will be managed sustainably under current and future conditions. It should be completed in conjunction with the Council's 'Completing your Pro Forma' document and your sustainable drainage system should be designed in accordance with [CIRIA The SuDS Manual C753](#).

The pro-forma follows Policy CS24 of [Knowsley MBC's Local Plan](#), [National Planning Policy Framework](#), [House of Commons Written Statement \(HWSW 161\) on SuDS](#), [Planning Practice Guidance](#) and [Defra's Non-Statutory Technical Standards for Sustainable Drainage Systems](#). It is supported by the [Defra/EA Guidance on Rainfall Runoff Management](#) and can be completed using freely available tools such as [Tools for Sustainable Drainage Systems](#) or approved Industry Standard surface water management design software. The Council's [Sustainable Drainage & Surface Water Management Technical Guidance document](#) also provides further information.

Section 1: Development Details

Development Name		Tarbock Green, Prescott			
Development Address (including postcode)		Sterling Inks UK Ltd, Netherley Road, Tarbock Green, Prescott, L35 1QE	Planning Application Reference (if available)		
Development Grid Reference	Northings	346365	Expected lifetime of development (years)	70-100 years (Residential)	
	Eastings	387663	Have you submitted a Flood Risk Assessment?	Yes ☒ No ☐	
Total Development Site Area (Ha)		0.80	Type of Planning Application (✓)	Outline	☒
Site area served by proposed drainage system (excluding open space) (Ha)*		0.80		Full	☐
Is your surface water drainage system designed to a (tick all that apply):				Hybrid	☐
Greenfield Standard		☒		Reserved Matters	☐
Previously Developed Standard		☐			

PRO-FORMA 1: Sustainable Drainage System: Planning Permission

Section 2: Impermeable Area and Existing Drainage For outline or reserved matters applications, go to Section 3

	Existing (E)	Proposed (P)	Difference (P – E)	Evidence Checklist	
Impermeable Area (Ha)	0.72	0.45	0.27	☒	Plans showing development layout of site with existing and proposed impermeable areas.
State Drainage Method	sewer	SuDS	N/A	☐	Plans showing current and proposed locations of sustainable drainage system.
Are there existing sewers, watercourses, water bodies, highway drains, soakaways or filter drains on the site?			Yes ☐ No ☒	☐	Plans showing existing layout to include: • Watercourses, open or culverted • Water bodies – ponds, swales etc. • Sewers, including manholes • Highway drains, include manholes • Soakaways, filter drains

Section 3: Surface Water Discharge Hierarchy – Planning Practice Guidance

Surface Water Discharge Method	Proposed?	If YES - Evidence Checklist		If NO - Evidence Checklist	
1. Infiltration to ground	Yes ☐ No ☒	☐	Completed Infiltration Checklist from CIRIA The SuDS Manual C753 Appendix B <i>An editable version of this form is available on SusDrain website.</i>	☐	Geotechnical Survey, including Soil Permeability Testing stating Percolation Coefficient, in accordance with BRE 365 AND Statement providing justification in your Sustainable Drainage Strategy
2. Discharge to watercourse or surface water body (Main River or Ordinary)	Yes ☐ No ☒	☐	Watercourse and/or Water Body Survey Report	☒	Plan showing nearby watercourses and water bodies AND Statement providing justification in your Sustainable Drainage Strategy
3. Discharge to surface water sewer	Yes ☒ No ☐	☐	Water and Sewerage Company written agreement for the Right to Connect.	☒	Plan showing nearby sewers AND
4. Discharge to combined sewer	Yes ☒ No ☐			☒	Statement providing justification in your Sustainable Drainage Strategy

PRO-FORMA 1: Sustainable Drainage System: Planning Permission

Section 4: Calculate Peak Discharge Rates – Technical Standards S2 and S3 (unless S1 applies)

Rainfall Event	Existing Rate (l/s)	Greenfield Rate (l/s)	Proposed Rate (l/s) <i>Brownfield sites must reduce discharge rates by 50%</i>	Evidence Checklist	
Qbar	12.90	5.29	5.29	☒	MicroDrainage (or equivalent) calculations
1:1 Year Event	11.54	4.74	5.29		
1:30 Year Event	26.84	11.19	5.29		
1:100 Year Event	35.85	15.26	5.29		

Section 5: Calculate Discharge Volume – Technical Standards S4 and S6 (unless S1 applies)

Rainfall Event	Existing Volume (m ³)	Greenfield Volume (m ³)	Proposed Volume (m ³)	Evidence Checklist	
1:100 Year 6 Hour Event				☐	MicroDrainage (or equivalent) calculations

Section 6: Infiltration

Site Information	✓	Evidence Checklist	
Do your sustainable drainage proposals include any infiltration?	Yes ☐ No ☒ <i>If NO, please move on to Section 7</i>	☐	Proposed sustainable drainage plans
You should submit an alternative 'Plan B' sustainable drainage design utilising an alternative discharge method if site specific ground conditions are unknown at this stage. This will become the default design in the event infiltration proposals are not feasible upon site specific ground investigation. Have you submitted an alternative 'Plan B' sustainable drainage design?	Yes ☐ No ☐	☐	'Plan B' conceptual sustainable drainage plans and statement of approach

PRO-FORMA 1: Sustainable Drainage System: Planning Permission

Section 7: Storage – Technical Standards S7, S8 and S9

Storage Details	Details	Evidence Checklist	
State climate change allowance used (%)	40%	☒	State / use in MicroDrainage
State storage volume provided (m ³) (excluding non-void spaces) <i>Must include an allowance for climate change and urban creep.</i>	240.00	☐	Drainage plans showing location of attenuation and all flow control devices and any supporting calculations
Summarise how storage will be provided for 1:30 year event on site. <i>Storage must be designed to ensure that at no flooding occurs onsite in a 1 in 30 year event except in designed areas and no flooding occurs offsite in a 1 in 100 year (+ climate change allowance) event.</i>	A total attenuation volume of 103.00 m ³ will be required to achieve the greenfield discharge rate of 5.34 l/s and to accommodate the 1 in 30 event. This will be provided in the form of an underground storage tank located in the southern extent of the Site or permeable paving in the private roads and driveways. A variable flow control can be installed within the storage system, this would reduce the storage size of the attenuation system. The location of attenuation tank should be confirmed at the detailed design stage and once a drainage survey has been undertaken.	☐	Plans showing size and location of storage and supporting calculations
Summarise how storage will be provided for 1:100 year (+ climate change) 6 hour event on site. <i>Where storage above the 1:30 year rainfall event is provided in designated areas designed to accommodate excess surface water volumes, plans showing storage locations and surface water depths and supported by MicroDrainage (or equivalent) calculations.</i>	A total attenuation volume of 240.00 m ³ will be required to achieve the greenfield discharge rate of 5.34 l/s and to accommodate the 1 in 100 plus 40 %CC event. This will be provided in the form of an underground storage tank located in the southern extent of the Site or permeable paving in the private roads and driveways. A variable flow control can be installed within the storage system, this would reduce the storage size of the attenuation system. The location of attenuation tank should be confirmed at the detailed design stage and once a drainage survey has been undertaken.	☐	Plans showing size and location of storage and supporting calculations

Section 8: Operation and Maintenance – Technical Standard S12 and HCWS161

Consideration	Select <u>ALL</u> that apply (✓)		Evidence Checklist
State how <u>ALL</u> components of the sustainable drainage system will be maintained for the design life of the development.	Sustainable drainage features are at property level	☐	☒ Statement provided within your Sustainable Drainage Strategy
	Sustainable drainage system to be adopted by Water and Sewerage Company through a Section 104 agreement (Water Industry Act 1991)	☐	
	Applicant to secure maintenance of sustainable drainage features by entering into a Section 106 agreement (Town and Country Planning Act 1990)	☒	

PRO-FORMA 1: Sustainable Drainage System: Planning Permission

Declaration and Submission

This pro-forma has been completed using evidence from information which has been submitted with my planning application.

The information submitted in the Sustainable Drainage Strategy and site-specific Flood Risk Assessment (FRA), where submitted, is proportionate to the site conditions, flood risks and magnitude of development and I agree that this information can be used as evidence to this sustainable drainage approach.

Submitter Details

Form <u>completed</u> by	Anoop Bains BSc MSc	Email Address	anoop.bains@deltasimons.com
		Daytime Telephone	07812 679487
Form <u>signed off</u> by	Joshua Rigby BSc MCIWEM	Accreditation(s) and/or Qualification(s) of Signatory	MCIWEM
Date (dd/mm/yyyy)	15/04/2020	Company	Delta -Simons

Client Details

Name	Jonathan Storey	Company	Pegasus Group
------	-----------------	---------	---------------